


JGB K 50/30 DA

Railing fastening channel for secure fastening of railing posts



The railing fastening channel JGB K 50/30 DA has general building authority approval and is made of hot-dip galvanised steel (fv) for indoor use or stainless steel (A4) for outdoor use. The railing fastening channel has a static load-bearing capacity of the normal force (NRd) of 17.2 kN and transverse force (VRd) of 17.2 kN. It is available in lengths of 100 to 250 mm and is paired with the bolts JB M12 - JB M20. The profile is 50 mm wide and 30 mm high. The filling is made of polyethylene (PE).

AbZ

steel, batch/hot-dip galvanized

Products	L	H _p	B _p		weight
JGBK5030DA FVK-0100	100 mm	30 mm	50 mm	2 Stk	0,629 kg
JGBK5030DA FVK-0120	120 mm	30 mm	50 mm	2 Stk	0,634 kg
JGBK5030DA FVK-0150	150 mm	30 mm	50 mm	2 Stk	0,722 kg
JGBK5030DA FVK-0200	200 mm	30 mm	50 mm	2 Stk	0,960 kg
JGBK5030DA FVK-0220	220 mm	30 mm	50 mm	2 Stk	1,026 kg
JGBK5030DA FVK-0250	250 mm	30 mm	50 mm	2 Stk	1,274 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L	H _p	B _p		weight
JGBK5030DA A4K-0100	100 mm	30 mm	50 mm	2 Stk	0,563 kg
JGBK5030DA A4K-0120	120 mm	30 mm	50 mm	2 Stk	0,622 kg
JGBK5030DA A4K-0150	150 mm	30 mm	50 mm	2 Stk	0,710 kg
JGBK5030DA A4K-0200	200 mm	30 mm	50 mm	2 Stk	0,856 kg
JGBK5030DA A4K-0220	220 mm	30 mm	50 mm	2 Stk	0,915 kg
JGBK5030DA A4K-0250	250 mm	30 mm	50 mm	2 Stk	1,138 kg

L: length
H_p: profile height

Page 1



PRODUCT INFORMATION

B_p: profile width



PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

