


JGB K 53/34 DA

Railing fastening channel for secure fastening of railing posts



The railing fastening channel JGB K 53/34 DA has general building authority approval and is made of hot-dip galvanised steel (fv) for indoor use or stainless steel (A4) for outdoor use. The railing fastening channel has a static load-bearing capacity of the normal force (NRd) of 30.6 kN and transverse force (VRd) of 30.6 kN. It is available in lengths of 100 to 250 mm and is paired with the bolts JB M16 - JB M20. The profile is 53 mm wide and 34 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	L	H _p	B _p		weight
JGBK5334DA FVK-0100	100 mm	34 mm	53 mm	2 Stk	1,168 kg
JGBK5334DA FVK-0120	120 mm	34 mm	53 mm	2 Stk	1,267 kg
JGBK5334DA FVK-0150	150 mm	34 mm	53 mm	2 Stk	1,415 kg
JGBK5334DA FVK-0200	200 mm	34 mm	53 mm	2 Stk	1,661 kg
JGBK5334DA FVK-0220	220 mm	34 mm	53 mm	2 Stk	1,760 kg
JGBK5334DA FVK-0250	250 mm	34 mm	53 mm	2 Stk	2,246 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L	H _p	B _p		weight
JGBK5334DA A4K-0100	100 mm	34 mm	53 mm	2 Stk	1,070 kg
JGBK5334DA A4K-0120	120 mm	34 mm	53 mm	2 Stk	1,244 kg
JGBK5334DA A4K-0150	150 mm	34 mm	53 mm	2 Stk	1,299 kg
JGBK5334DA A4K-0200	200 mm	34 mm	53 mm	2 Stk	1,528 kg
JGBK5334DA A4K-0220	220 mm	34 mm	53 mm	2 Stk	1,619 kg
JGBK5334DA A4K-0250	250 mm	34 mm	53 mm	2 Stk	2,063 kg

L: length
H_p: profile height

Page 1



B_p: profile width

AbZ

