


JH M12

Tee-head bolt



JH M12 have European Technical Assessment ETA-09/0338. They are used to fasten companion structures to K 38/17, K 36/36, K 36/20 anchor channels and mounting channels. They have a hammer-shaped head and a notch at the end of the shaft. The bolts are made of hot-dip galvanised steel, galvanised steel or stainless steel and are available in various lengths. The JH M12 are supplied with the nuts.



stainless steel, UNS S31803

| Products | L | W |
|---------------|-------|----------|
| JH1230 A4-70I | 30 mm | 0,063 kg |
| JH1250 A4-70I | 50 mm | 0,077 kg |
| JH1260 A4-70I | 60 mm | 0,085 kg |
| JH1280 FA-70 | 80 mm | 0,101 kg |

steel, galvanic zinc plated

| Products | L | W |
|------------|--------|-----------------|
| JH1220 GV | 20 mm | 4,6 0,056 kg |
| JH1230 GV | 30 mm | 4,6 0,063 kg |
| JH1240 GV | 40 mm | 4,6 0,071 kg |
| JH1250 GV | 50 mm | 4,6 0,078 kg |
| JH1260 GV | 60 mm | 4,6 0,085 kg |
| JH1280 GV | 80 mm | 4,6 0,100 kg |
| JH12100 GV | 100 mm | 4,6 0,114 kg |
| JH12125 GV | 125 mm | 4,6 0,132 kg |
| JH12150 GV | 150 mm | 8,8 0,150 kg |
| JH12200 GV | 200 mm | 4,6 0,187 kg |



PRODUCT INFORMATION

steel, batch/hot-dip galvanized

| Products | L | | W |
|----------------|--------|-----|----------|
| JH1230 FV | 30 mm | 4,6 | 0,068 kg |
| JH1240 FV | 40 mm | 4,6 | 0,075 kg |
| JH1250 FV | 50 mm | 4,6 | 0,082 kg |
| JH1260 FV | 60 mm | 4,6 | 0,089 kg |
| JH1280 FV | 80 mm | 4,6 | 0,104 kg |
| JH12100 8.8 FV | 100 mm | 8,8 | 0,118 kg |
| JH12100 FV | 100 mm | 4,6 | 0,118 kg |
| JH12125 FV | 125 mm | 4,6 | 0,137 kg |

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

| Products | L | | W |
|--------------|--------|--|----------|
| JH1240 A4-70 | 40 mm | | 0,072 kg |
| JH12100 A4 | 100 mm | | 0,115 kg |
| JH12150 A4 | 150 mm | | 0,151 kg |
| JH12200 A4 | 200 mm | | 0,188 kg |

L: length

W: Weight per storage unit



, ETA-09/0338

