



JM K 50/30

Mounting channels, cold-formed

The mounting channel JM K 50/30 has environmental product declaration EPD-JDL-20200260-IBB1-DE and is made of hot-dip galvanised steel (fv), stainless steel (A4) or rolled plain steel (wb). It has a static load-bearing capacity of the normal force (NRd) of 16.8 kN. The mounting channel is available in the standard length of 6000 mm and is paired with the bolts JB M10 - JB M20. The profile is 50 mm wide and 30 mm high.



steel, bright rolled

| Products | L | H _p | B _p | A | W |
|----------------|---------|----------------|----------------|-----------------------|-----------|
| JMK5030 R-6000 | 6000 mm | 30 mm | 50 mm | 3,839 cm ² | 18,078 kg |

steel, batch/hot-dip galvanized

| Products | L | H _p | B _p | A | W |
|-----------------|---------|----------------|----------------|-----------------------|-----------|
| JMK5030 FV-6000 | 6000 mm | 30 mm | 50 mm | 3,839 cm ² | 19,884 kg |

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

| Products | L | H _p | B _p | A | W |
|-----------------|---------|----------------|----------------|-----------------------|-----------|
| JMK5030 A4-6000 | 6000 mm | 30 mm | 50 mm | 3,839 cm ² | 17,592 kg |

L: length
H_p: profile height
B_p: profile width
A: cross section area
W: Weight per storage unit



OPTIONAL ACCESSORIES

JGM B



, EPD-JDL-20200260-IBB1-DE

