

# JM W 40/22

Mounting channels, hot-rolled

The mounting channel JM W 40/22 is approved throughout Europe by ETA-15/0386. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE and is made of hot-dip galvanised steel (fv), stainless steel (A4) and rolled plain steel (wb). This mounting channel has a static load-bearing capacity of the normal force (NRd) of 11.7 kN and shear force (VRd) of 11.4 kN. It is available with a total length of 6000 mm and is paired with the bolts JC M10 - JC M16. The profile is 40 mm wide and 22 mm high.



### steel, bright rolled

Products	L	$H_P$	$B_{P}$	Α	weight
JMW4022 R-6000	6000 mm	22 mm	40 mm	2,746 cm <sup>2</sup>	12,936 kg

### steel, batch/hot-dip galvanized

Products	L	H <sub>P</sub>	B <sub>P</sub>	А	weight
JMW4022 FV-6000	6000 mm	22 mm	40 mm	2,746 cm <sup>2</sup>	14,040 kg

#### Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L	H <sub>P</sub>	B <sub>P</sub>	A	weight
JMW4022 A4-6000	6000 mm	22 mm	40 mm	2,746 cm <sup>2</sup>	13,182 kg

L: length

H<sub>p</sub>: profile height B<sub>p</sub>: profile width A: cross section area

Page 1





# PRODUCT INFORMATION

## **OPTIONAL ACCESSORIES**

JGM C



, ETA-15/0386



, EPD-JDL-20200260-IBB1-DE





Page 2