



## JM W 50/30

Mounting channels, hot-rolled

The mounting channel JM W 50/30 is approved throughout Europe by ETA-15/0386. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE and is made of hot-dip galvanised steel (fv), stainless steel (A4) and rolled plain steel (wb). This mounting channel has a static load-bearing capacity of the normal force (NRd) of 20.6 kN and shear force (VRd) of 20.2 kN. It is available with a total length of 6000 mm and is paired with the bolts JB M10 - JB M20. The profile is 50 mm wide and 30 mm high.



### steel, bright rolled

Products	L	H <sub>p</sub>	B <sub>p</sub>	A	weight
JMW5030 R-6000	6000 mm	30 mm	50 mm	4,204 cm <sup>2</sup>	19,800 kg

### steel, batch/hot-dip galvanized

Products	L	H <sub>p</sub>	B <sub>p</sub>	A	weight
JMW5030 FV-6000	6000 mm	30 mm	50 mm	4,204 cm <sup>2</sup>	21,540 kg

### Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L	H <sub>p</sub>	B <sub>p</sub>	A	weight
JMW5030 A4-6000	6000 mm	30 mm	50 mm	4,204 cm <sup>2</sup>	20,178 kg

L: length  
H<sub>p</sub>: profile height  
B<sub>p</sub>: profile width  
A: cross section area



## OPTIONAL ACCESSORIES

JGM B

ETA

, ETA-15/0386



, EPD-JDL-20200260-IBB1-DE

