



JM W 72/48

Mounting channels, hot-rolled

The mounting channel JM W 72/48 is approved throughout Europe by ETA-15/0386. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE and is made of hot-dip galvanized steel (fv), stainless steel (A4) and rolled plain steel (wb). This mounting channel has a static load-bearing capacity of the normal force (NRd) of 66.1 kN and shear force (VRd) of 65.8 kN. It is available with a total length of 6000 mm and is paired with the bolts JA M20 - JA M30. The profile is 72 mm wide and 48 mm high.



steel, bright rolled

Products	L	H _p	B _p	A	weight
JMW7248 R-6000	6000 mm	48 mm	72 mm	11,265 cm ²	53,058 kg

steel, batch/hot-dip galvanized

Products	L	H _p	B _p	A	weight
JMW7248 FV-6000	6000 mm	48 mm	72 mm	11,265 cm ²	58,362 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L	H _p	B _p	A	weight
JMW7248 A4-6000	6000 mm	48 mm	72 mm	11,265 cm ²	54,072 kg

L: length
H_p: profile height
B_p: profile width
A: cross section area



OPTIONAL ACCESSORIES

JGM A



, ETA-15/0386



, EPD-JDL-20200260-IBB1-DE

