



JML K 28/15

Mounting channels, cold-formed, perforated

The mounting channel JML K 28/15 has environmental product declaration EPD-JDL-20200260-IBB1-DE and is made of hot-dip galvanized steel (fv), stainless steel (A4) or rolled plain steel (wb). It has a static load-bearing capacity of the normal force (NRd) of 4.9 kN. The mounting channel is available in lengths of 100 to 6000 mm and is paired with the bolts JD M6 - JD M12. The profile is 28 mm wide and 15 mm high.



steel, bright rolled

Products	L	H _p	B _p	A	weight
LSK2815 R-6000	6000 mm	15 mm	28 mm	1,21 cm ²	6,120 kg

steel, batch/hot-dip galvanized

Products	L	H _p	B _p	A	weight
LSK2815 FV-6000	6000 mm	15 mm	28 mm	1,21 cm ²	6,732 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L	H _p	B _p	A	weight
LSK2815 A4-6000	6000 mm	15 mm	28 mm	1,21 cm ²	6,240 kg

L: length
H_p: profile height
B_p: profile width
A: cross section area



OPTIONAL ACCESSORIES

JGM D, JMA Series 12, JMA-D Series 12, JMA-Q Series 12, JMA-QE Series 12, JNA Series 12, JVB-Z, JVB-ZS



, EPD-JDL-20200260-IBB1-DE

