



JML K 40/25

Mounting channels, cold-formed, perforated

The mounting channel JML K 40/25 has environmental product declaration EPD-JDL-20200260-IBB1-DE and is made of hot-dip galvanised steel (fv), stainless steel (A4) or rolled plain steel (wb). It has a static load-bearing capacity of the normal force (NRd) of 11.2 kN. The mounting channel is available in lengths of 100 to 6000 mm and is paired with the bolts JC M10 - JC M16. The profile is 40 mm wide and 25 mm high.



steel, bright rolled

Products	L	H _p	B _p	A	W
LSK4025 R-6000	6000 mm	25 mm	40 mm	2,356 cm ²	11,160 kg

steel, batch/hot-dip galvanized

Products	L	H _p	B _p	A	W
LSK4025 FV-6000	6000 mm	25 mm	40 mm	2,356 cm ²	13,200 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L	H _p	B _p	A	W
LSK4025 A4-6000	6000 mm	25 mm	40 mm	2,356 cm ²	11,382 kg

L: length
H_p: profile height
B_p: profile width
A: cross section area
W: Weight per storage unit



OPTIONAL ACCESSORIES

JGM C



, EPD-JDL-20200260-IBB1-DE

