

JTA K 28/15

Anchor channel, cold-formed, with round or I anchor



The anchor channel JTA K 28/15 is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanized steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JD M6 - JD M12. The profile is 28 mm wide and 15 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	H	L	H _p	B _p		W
JTAK2815-0100-FVKCE	50 mm	100 mm	15 mm	28 mm	2 Stk	0,152 kg
JTAK2815-0150-FVKCE	50 mm	150 mm	15 mm	28 mm	2 Stk	0,213 kg
JTAK2815-0200-FVKCE	50 mm	200 mm	15 mm	28 mm	2 Stk	0,274 kg
JTAK2815-0250-FVKCE	50 mm	250 mm	15 mm	28 mm	2 Stk	0,335 kg
JTAK2815-0300-FVKCE	50 mm	300 mm	15 mm	28 mm	3 Stk	0,411 kg
JTAK2815-0350-FVKCE	50 mm	350 mm	15 mm	28 mm	3 Stk	0,472 kg
JTAK2815-0400-FVKCE	50 mm	400 mm	15 mm	28 mm	3 Stk	0,533 kg
JTAK2815-0550-FVKCE	50 mm	550 mm	15 mm	28 mm	4 Stk	0,732 kg
JTAK2815-0800-FVKCE	50 mm	800 mm	15 mm	28 mm	5 Stk	1,052 kg
JTAK2815-1050-FVKCE	50 mm	1050 mm	15 mm	28 mm	6 Stk	1,373 kg
JTAK2815-3000-FVKCE	50 mm	3000 mm	15 mm	28 mm	16 Stk	3,907 kg
JTAK2815-6000-FVKCE	50 mm	6000 mm	15 mm	28 mm	31 Stk	1,300 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	H _p	B _p		W
JTAK2815-0100-A4KCE	50 mm	100 mm	15 mm	28 mm	2 Stk	0,140 kg
JTAK2815-0150-A4KCE	50 mm	150 mm	15 mm	28 mm	2 Stk	0,197 kg
JTAK2815-0200-A4KCE	50 mm	200 mm	15 mm	28 mm	2 Stk	0,254 kg
JTAK2815-0250-A4KCE	50 mm	250 mm	15 mm	28 mm	2 Stk	0,310 kg



PRODUCT INFORMATION

Products	H	L	H _p	B _p		W
JTAK2815-0300-A4KCE	50 mm	300 mm	15 mm	28 mm	3 Stk	0,381 kg
JTAK2815-0350-A4KCE	50 mm	350 mm	15 mm	28 mm	3 Stk	0,438 kg
JTAK2815-0400-A4KCE	50 mm	400 mm	15 mm	28 mm	3 Stk	0,494 kg
JTAK2815-0550-A4KCE	50 mm	550 mm	15 mm	28 mm	4 Stk	0,678 kg
JTAK2815-0800-A4KCE	50 mm	800 mm	15 mm	28 mm	5 Stk	0,975 kg
JTAK2815-1050-A4KCE	50 mm	1050 mm	15 mm	28 mm	6 Stk	1,272 kg
JTAK2815-3000-A4KCE	50 mm	3000 mm	15 mm	28 mm	16 Stk	3,621 kg
JTAK2815-6000-A4KCE	50 mm	6000 mm	15 mm	28 mm	31 Stk	1,205 kg

H: installation height

L: length

H_p: profile height

B_p: profile width

W: Weight per storage unit

OPTIONAL ACCESSORIES

JGM D, JSV28, JMA Series 12, JMA-D Series 12, JMA-Q Series 12, JMA-QE Series 12, JNA Series 12, JVB-Z, JVB-ZS

ETA

, ETA-09/0338



, EPD-JDL-20200260-IBB1-DE

