



## JTA K 38/17

Anchor channel, cold-formed, with round or I anchor

The anchor channel JTA K 38/17 is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JH M10 - JH M16. The profile is 38 mm wide and 17 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	H	L	H <sub>p</sub>	B <sub>p</sub>		W
JTAK3817-0100-FVKCE	80 mm	100 mm	17 mm	38 mm	2 Stk	0,288 kg
JTAK3817-0150-FVKCE	80 mm	150 mm	17 mm	38 mm	2 Stk	0,387 kg
JTAK3817-0200-FVKCE	80 mm	200 mm	17 mm	38 mm	2 Stk	0,487 kg
JTAK3817-0250-FVKCE	80 mm	250 mm	17 mm	38 mm	2 Stk	0,586 kg
JTAK3817-0300-FVKCE	80 mm	300 mm	17 mm	38 mm	3 Stk	0,730 kg
JTAK3817-0350-FVKCE	80 mm	350 mm	17 mm	38 mm	3 Stk	0,830 kg
JTAK3817-0400-FVKCE	80 mm	400 mm	17 mm	38 mm	3 Stk	0,929 kg
JTAK3817-0550-FVKCE	80 mm	550 mm	17 mm	38 mm	4 Stk	1,272 kg
JTAK3817-0800-FVKCE	80 mm	800 mm	17 mm	38 mm	5 Stk	1,814 kg
JTAK3817-1050-FVKCE	80 mm	1050 mm	17 mm	38 mm	6 Stk	2,355 kg
JTAK3817-3000-FVKCE	80 mm	3000 mm	17 mm	38 mm	16 Stk	6,679 kg
JTAK3817-6000-FVKCE	80 mm	6000 mm	17 mm	38 mm	31 Stk	2,219 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	H <sub>p</sub>	B <sub>p</sub>		W
JTAK3817-0100-A4KCE	80 mm	100 mm	17 mm	38 mm	2 Stk	0,264 kg
JTAK3817-0150-A4KCE	80 mm	150 mm	17 mm	38 mm	2 Stk	0,356 kg
JTAK3817-0200-A4KCE	80 mm	200 mm	17 mm	38 mm	2 Stk	0,449 kg
JTAK3817-0250-3A-A4KCE	80 mm	250 mm	17 mm	38 mm		0,581 kg

Page 1



# PRODUCT INFORMATION

Products	H	L	H <sub>p</sub>	B <sub>p</sub>		W
JTAK3817-0250-A4KCE	80 mm	250 mm	17 mm	38 mm	2 Stk	0,541 kg
JTAK3817-0300-A4KCE	80 mm	300 mm	17 mm	38 mm	3 Stk	0,673 kg
JTAK3817-0350-A4KCE	80 mm	350 mm	17 mm	38 mm	3 Stk	0,765 kg
JTAK3817-0400-A4KCE	80 mm	400 mm	17 mm	38 mm	3 Stk	0,857 kg
JTAK3817-0550-A4KCE	80 mm	550 mm	17 mm	38 mm	4 Stk	1,174 kg
JTAK3817-0800-A4KCE	80 mm	800 mm	17 mm	38 mm	5 Stk	1,674 kg
JTAK3817-1050-A4KCE	80 mm	1050 mm	17 mm	38 mm	6 Stk	2,175 kg
JTAK3817-3000-A4KCE	80 mm	3000 mm	17 mm	38 mm	16 Stk	6,169 kg
JTAK3817-6000-A4KCE	80 mm	6000 mm	17 mm	38 mm	31 Stk	2,050 kg

**H:** installation height  
**L:** length  
**H<sub>p</sub>:** profile height  
**B<sub>p</sub>:** profile width  
**W:** Weight per storage unit

## OPTIONAL ACCESSORIES

JGM H, JSV38, JVL, JKZS, JMA Series 18, JMA-Q Series 18, JMA-QE Series 18, JNA Series 18, JVB-Z, JVB-ZS



, ETA-09/0338



, EPD-JDL-20200260-IBB1-DE

