



JTA K 53/34

Anchor channel, cold-formed, with round or I anchor

The JTA K 53/34 anchor channel is approved throughout Europe by ETA-09/0338. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanized steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JB M10 - JB M20. The profile is 53 mm wide and 34 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	H	L	H _p	B _p		W
JTAK5334-0150-FVKCE	170 mm	150 mm	34 mm	53 mm	2 Stk	1,065 kg
JTAK5334-0200-FVKCE	170 mm	200 mm	34 mm	53 mm	2 Stk	1,312 kg
JTAK5334-0250-FVKCE	170 mm	250 mm	34 mm	53 mm	2 Stk	1,559 kg
JTAK5334-0300-3A-FVKCE	170 mm	300 mm	34 mm	53 mm	1,968 kg	
JTAK5334-0300-FVKCE	170 mm	300 mm	34 mm	53 mm	2 Stk	1,805 kg
JTAK5334-0350-FVKCE	170 mm	350 mm	34 mm	53 mm	3 Stk	2,215 kg
JTAK5334-0400-FVKCE	170 mm	400 mm	34 mm	53 mm	3 Stk	2,462 kg
JTAK5334-0550-FVKCE	170 mm	550 mm	34 mm	53 mm	3 Stk	3,202 kg
JTAK5334-0800-FVKCE	170 mm	800 mm	34 mm	53 mm	4 Stk	4,598 kg
JTAK5334-1050-FVKCE	170 mm	1050 mm	34 mm	53 mm	5 Stk	5,995 kg
JTAK5334-3000-FVKCE	170 mm	3000 mm	34 mm	53 mm	13 Stk	16,920 kg
JTAK5334-6000-FVKCE	170 mm	6000 mm	34 mm	53 mm	25 Stk	5,613 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	H _p	B _p		W
JTAK5334-0150-A4KCE	170 mm	150 mm	34 mm	53 mm	2 Stk	0,939 kg
JTAK5334-0200-A4KCE	170 mm	200 mm	34 mm	53 mm	2 Stk	1,170 kg
JTAK5334-0250-A4KCE	170 mm	250 mm	34 mm	53 mm	2 Stk	1,400 kg
JTAK5334-0300-A4KCE	170 mm	300 mm	34 mm	53 mm	3 Stk	1,630 kg



PRODUCT INFORMATION

Products	H	L	H _p	B _p		W
JTAK5334-0350-A4KCE	170 mm	350 mm	34 mm	53 mm	3 Stk	1,980 kg
JTAK5334-0400-A4KCE	170 mm	400 mm	34 mm	53 mm	3 Stk	2,210 kg
JTAK5334-0550-A4KCE	170 mm	550 mm	34 mm	53 mm	3 Stk	2,900 kg
JTAK5334-0800-A4KCE	170 mm	800 mm	34 mm	53 mm	4 Stk	4,170 kg
JTAK5334-1050-A4KCE	170 mm	1050 mm	34 mm	53 mm	5 Stk	5,440 kg
JTAK5334-3000-A4KCE	170 mm	3000 mm	34 mm	53 mm	13 Stk	15,370 kg
JTAK5334-6000-A4KCE	170 mm	6000 mm	34 mm	53 mm	25 Stk	5,101 kg

H: installation height
L: length
H_p: profile height
B_p: profile width
W: Weight per storage unit

OPTIONAL ACCESSORIES

JGM B



, ETA-09/0338



, EPD-JDL-20200260-IBB1-DE

