



## JTA K 72/48

Anchor channel, cold-formed, with round or I anchor

The JTA K 72/48 anchor channel is approved throughout Europe by ETA-09/0338. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanised steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JA M20 - JA M30. The profile is 72 mm wide and 48 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	H	L	H <sub>p</sub>	B <sub>p</sub>	W	
JTAK7248-0150-FVKCE	195 mm	150 mm	48 mm	72 mm	2 Stk	1,941 kg
JTAK7248-0200-FVKCE	195 mm	200 mm	48 mm	72 mm	2 Stk	2,387 kg
JTAK7248-0250-FVKCE	195 mm	250 mm	48 mm	72 mm	2 Stk	2,832 kg
JTAK7248-0300-FVKCE	195 mm	300 mm	48 mm	72 mm	2 Stk	3,278 kg
JTAK7248-0350-FVKCE	195 mm	350 mm	48 mm	72 mm	2 Stk	3,724 kg
JTAK7248-0400-FVKCE	195 mm	400 mm	48 mm	72 mm	3 Stk	4,472 kg
JTAK7248-0550-FVKCE	195 mm	550 mm	48 mm	72 mm	3 Stk	5,810 kg
JTAK7248-0800-FVKCE	195 mm	800 mm	48 mm	72 mm	4 Stk	8,341 kg
JTAK7248-1050-FVKCE	195 mm	1050 mm	48 mm	72 mm	5 Stk	10,872 kg
JTAK7248-6000-FVKCE	195 mm	6000 mm	48 mm	72 mm	21 Stk	9,974 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	H <sub>p</sub>	B <sub>p</sub>	W	
JTAK7248-6000-A4KCE	195 mm	6000 mm	48 mm	72 mm	21 Stk	9,241 kg

**H:** installation height

**L:** length

**H<sub>p</sub>:** profile height

**B<sub>p</sub>:** profile width



W: Weight per storage unit

## OPTIONAL ACCESSORIES

JGM A



, ETA-09/0338



, EPD-JDL-20200260-IBB1-DE

