



JTA W 40/22

Anchor channel, hot-rolled, with round or I anchor

The anchor channel JTA W 40/22 is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanised steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JC M10 - JC M16. The profile is 40 mm wide and 22 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	H	L	H _p	B _p		weight
JTAW4022-0150-FVKCE	90 mm	150 mm	22 mm	40 mm	2 Stk	0,441 kg
JTAW4022-0200-FVKCE	90 mm	200 mm	22 mm	40 mm	2 Stk	0,558 kg
JTAW4022-0250-3A-FVKCE	90 mm	250 mm	22 mm	40 mm	3 Stk	0,720 kg
JTAW4022-0250-FVKCE	90 mm	250 mm	22 mm	40 mm	2 Stk	0,675 kg
JTAW4022-0300-3A-FVKCE	90 mm	300 mm	22 mm	40 mm	3 Stk	0,837 kg
JTAW4022-0300-FVKCE	90 mm	300 mm	22 mm	40 mm	2 Stk	0,792 kg
JTAW4022-0350-FVKCE	90 mm	350 mm	22 mm	40 mm	3 Stk	0,954 kg
JTAW4022-0400-FVKCE	90 mm	400 mm	22 mm	40 mm	3 Stk	1,071 kg
JTAW4022-0550-FVKCE	90 mm	550 mm	22 mm	40 mm	3 Stk	1,422 kg
JTAW4022-0800-FVKCE	90 mm	800 mm	22 mm	40 mm	4 Stk	2,052 kg
JTAW4022-1050-FVKCE	90 mm	1050 mm	22 mm	40 mm	5 Stk	2,682 kg
JTAW4022-3000-FVKCE	90 mm	3000 mm	22 mm	40 mm	13 Stk	7,607 kg
JTAW4022-6000-FVKCE	90 mm	6000 mm	22 mm	40 mm	25 Stk	2,528 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	H _p	B _p		weight
JTAW4022-0150-A4KCE	90 mm	150 mm	22 mm	40 mm	2 Stk	0,403 kg
JTAW4022-0200-A4KCE	90 mm	200 mm	22 mm	40 mm	2 Stk	0,511 kg
JTAW4022-0250-A4KCE	90 mm	250 mm	22 mm	40 mm	2 Stk	0,618 kg



PRODUCT INFORMATION

Products	H	L	H _p	B _p		weight
JTAW4022-0300-A4KCE	90 mm	300 mm	22 mm	40 mm	2 Stk	0,726 kg
JTAW4022-0350-A4KCE	90 mm	350 mm	22 mm	40 mm	3 Stk	0,874 kg
JTAW4022-0400-A4KCE	90 mm	400 mm	22 mm	40 mm	3 Stk	0,982 kg
JTAW4022-0550-A4KCE	90 mm	550 mm	22 mm	40 mm	3 Stk	1,304 kg
JTAW4022-0800-A4KCE	90 mm	800 mm	22 mm	40 mm	4 Stk	1,883 kg
JTAW4022-1050-A4KCE	90 mm	1050 mm	22 mm	40 mm	5 Stk	2,461 kg
JTAW4022-3000-A4KCE	90 mm	3000 mm	22 mm	40 mm	13 Stk	6,981 kg
JTAW4022-6000-A4KCE	90 mm	6000 mm	22 mm	40 mm	25 Stk	2,320 kg

H: installation height

L: length

H_p: profile height

B_p: profile width

OPTIONAL ACCESSORIES

JGM C, JSV40, JVL, JKZS

ETA

, ETA-09/0338



, EPD-JDL-20200260-IBB1-DE

