



## JTA W 40+

Anchor channel, hot-rolled, with round or I anchor

The anchor channel JTA W 40+ is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanised steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JC M10 - JC M16. The profile is 40 mm wide and 22 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	H	L	H <sub>p</sub>	B <sub>p</sub>	W	
JTAW40+0150-FVKCE	100 mm	150 mm	22 mm	40 mm	2 Stk	0,488 kg
JTAW40+0200-FVKCE	100 mm	150 mm	22 mm	40 mm	2 Stk	0,604 kg
JTAW40+0250-FVKCE	100 mm	150 mm	22 mm	40 mm	2 Stk	0,720 kg
JTAW40+0300-FVKCE	100 mm	150 mm	22 mm	40 mm	2 Stk	0,836 kg
JTAW40+0350-FVKCE	100 mm	150 mm	22 mm	40 mm	3 Stk	1,022 kg
JTAW40+0400-FVKCE	100 mm	150 mm	22 mm	40 mm	3 Stk	1,138 kg
JTAW40+0550-FVKCE	100 mm	150 mm	22 mm	40 mm	3 Stk	1,485 kg
JTAW40+0800-FVKCE	100 mm	150 mm	22 mm	40 mm	4 Stk	2,134 kg
JTAW40+1050-FVKCE	100 mm	150 mm	22 mm	40 mm	5 Stk	2,784 kg
JTAW40+3000-FVKCE	100 mm	150 mm	22 mm	40 mm	13 Stk	7,864 kg
JTAW40+6000-FVKCE	100 mm	6000 mm	22 mm	40 mm	25 Stk	2,760 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	H <sub>p</sub>	B <sub>p</sub>	W	
JTAW40+0150-A4KCE	100 mm	150 mm	22 mm	40 mm	2 Stk	0,413 kg
JTAW40+0200-A4KCE	100 mm	200 mm	22 mm	40 mm	2 Stk	0,520 kg
JTAW40+0250-A4KCE	100 mm	250 mm	22 mm	40 mm	2 Stk	0,628 kg
JTAW40+0300-A4KCE	100 mm	300 mm	22 mm	40 mm	2 Stk	0,736 kg
JTAW40+0350-A4KCE	100 mm	350 mm	22 mm	40 mm	3 Stk	0,888 kg

Page 1



# PRODUCT INFORMATION

---

Products	H	L	H <sub>p</sub>	B <sub>p</sub>		W
JTAW40+0400-A4KCE	100 mm	400 mm	22 mm	40 mm	3 Stk	0,996 kg
JTAW40+0550-A4KCE	100 mm	550 mm	22 mm	40 mm	3 Stk	1,319 kg
JTAW40+0800-A4KCE	100 mm	800 mm	22 mm	40 mm	4 Stk	1,902 kg
JTAW40+1050-A4KCE	100 mm	1050 mm	22 mm	40 mm	5 Stk	2,485 kg
JTAW40+3000-A4KCE	100 mm	3000 mm	22 mm	40 mm	13 Stk	7,041 kg
JTAW40+6000-A4KCE	100 mm	6000 mm	22 mm	40 mm	25 Stk	2,400 kg

**H:** installation height

**L:** length

**H<sub>p</sub>:** profile height

**B<sub>p</sub>:** profile width

**W:** Weight per storage unit

## OPTIONAL ACCESSORIES

JGM C, JSV40, JVL, JKZS



, ETA-09/0338



, EPD-JDL-20200260-IBB1-DE

