



## JTA W 50/30

Anchor channel, hot-rolled, with round or I anchor

The anchor channel JTA W 50/30 is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanized steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JB M10 - JB M20. The profile is 50 mm wide and 30 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	H	L	H <sub>p</sub>	B <sub>p</sub>		weight
JTAW5030-0150-FVKCE	100 mm	150 mm	30 mm	50 mm	2 Stk	0,684 kg
JTAW5030-0200-FVKCE	100 mm	200 mm	30 mm	50 mm	2 Stk	0,864 kg
JTAW5030-0250-FVKCE	100 mm	250 mm	30 mm	50 mm	2 Stk	1,043 kg
JTAW5030-0300-3A-FVKCE	100 mm	300 mm	30 mm	50 mm	1,296 kg	
JTAW5030-0300-FVKCE	100 mm	300 mm	30 mm	50 mm	2 Stk	1,223 kg
JTAW5030-0350-FVKCE	100 mm	350 mm	30 mm	50 mm	3 Stk	1,475 kg
JTAW5030-0400-FVKCE	100 mm	400 mm	30 mm	50 mm	3 Stk	1,655 kg
JTAW5030-0550-FVKCE	100 mm	550 mm	30 mm	50 mm	3 Stk	2,193 kg
JTAW5030-0800-FVKCE	100 mm	800 mm	30 mm	50 mm	4 Stk	3,164 kg
JTAW5030-1050-FVKCE	100 mm	1050 mm	30 mm	50 mm	5 Stk	4,135 kg
JTAW5030-3000-FVKCE	100 mm	3000 mm	30 mm	50 mm	13 Stk	11,720 kg
JTAW5030-6000-FVKCE	100 mm	6000 mm	30 mm	50 mm	25 Stk	3,895 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	H <sub>p</sub>	B <sub>p</sub>		weight
JTAW5030-0150-A4KCE	100 mm	150 mm	30 mm	50 mm	2 Stk	0,607 kg
JTAW5030-0200-A4KCE	100 mm	200 mm	30 mm	50 mm	2 Stk	0,772 kg
JTAW5030-0250-A4KCE	100 mm	250 mm	30 mm	50 mm	2 Stk	0,936 kg
JTAW5030-0300-3A-A4KCE	100 mm	300 mm	30 mm	50 mm	2 Stk	1,108 kg



# PRODUCT INFORMATION

---

Products	H	L	H <sub>p</sub>	B <sub>p</sub>		weight
JTAW5030-0300-A4KCE	100 mm	300 mm	30 mm	50 mm	2 Stk	1,102 kg
JTAW5030-0350-A4KCE	100 mm	350 mm	30 mm	50 mm	3 Stk	1,322 kg
JTAW5030-0400-A4KCE	100 mm	400 mm	30 mm	50 mm	3 Stk	1,487 kg
JTAW5030-0550-A4KCE	100 mm	550 mm	30 mm	50 mm	3 Stk	1,982 kg
JTAW5030-0800-A4KCE	100 mm	800 mm	30 mm	50 mm	4 Stk	2,862 kg
JTAW5030-1050-A4KCE	100 mm	1050 mm	30 mm	50 mm	5 Stk	3,741 kg
JTAW5030-3000-A4KCE	100 mm	3000 mm	30 mm	50 mm	13 Stk	10,616 kg
JTAW5030-6000-A4KCE	100 mm	6000 mm	30 mm	50 mm	25 Stk	3,529 kg

**H:** installation height

**L:** length

**H<sub>p</sub>:** profile height

**B<sub>p</sub>:** profile width

## OPTIONAL ACCESSORIES

JGM B, JSV50, JKZS

ETA

, ETA-09/0338



, EPD-JDL-20200260-IBB1-DE

