



JTA W 53/34

Anchor channel, hot-rolled, with round or I anchor

The anchor channel JTA W 53/34 is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanised steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JB M10 - JB M20. The profile is 53 mm wide and 34 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	H	L	H _p	B _p		weight
JTAW5334-0150-FVKCE	170 mm	150 mm	34 mm	53 mm	2 Stk	1,146 kg
JTAW5334-0200-FVKCE	170 mm	200 mm	34 mm	53 mm	2 Stk	1,419 kg
JTAW5334-0250-FVKCE	170 mm	250 mm	34 mm	53 mm	2 Stk	1,693 kg
JTAW5334-0300-3A-FVKCE	170 mm	300 mm	34 mm	53 mm	2,129 kg	
JTAW5334-0300-FVKCE	170 mm	300 mm	34 mm	53 mm	3 Stk	1,967 kg
JTAW5334-0350-FVKCE	170 mm	350 mm	34 mm	53 mm	3 Stk	2,403 kg
JTAW5334-0400-FVKCE	170 mm	400 mm	34 mm	53 mm	3 Stk	2,677 kg
JTAW5334-0550-FVKCE	170 mm	550 mm	34 mm	53 mm	3 Stk	3,300 kg
JTAW5334-0800-FVKCE	170 mm	800 mm	34 mm	53 mm	4 Stk	5,029 kg
JTAW5334-1050-FVKCE	170 mm	1050 mm	34 mm	53 mm	5 Stk	6,560 kg
JTAW5334-3000-FVKCE	170 mm	3000 mm	34 mm	53 mm	13 Stk	18,534 kg
JTAW5334-6000-FVKCE	170 mm	6000 mm	34 mm	53 mm	25 Stk	6,151 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	H _p	B _p		weight
JTAW5334-0150-A4KCE	170 mm	350 mm	34 mm	53 mm	2 Stk	1,020 kg
JTAW5334-0200-A4KCE	170 mm	350 mm	34 mm	53 mm	2 Stk	1,270 kg
JTAW5334-0250-A4KCE	170 mm	250 mm	34 mm	53 mm	2 Stk	1,521 kg
JTAW5334-0300-A4KCE	170 mm	350 mm	34 mm	53 mm	3 Stk	1,770 kg



PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com



PRODUCT INFORMATION

Products	H	L	H _p	B _p		weight
JTAW5334-0350-A4KCE	170 mm	350 mm	34 mm	53 mm	3 Stk	2,154 kg
JTAW5334-0400-A4KCE	170 mm	350 mm	34 mm	53 mm	3 Stk	2,410 kg
JTAW5334-0550-A4KCE	170 mm	350 mm	34 mm	53 mm	3 Stk	3,170 kg
JTAW5334-0800-A4KCE	170 mm	350 mm	34 mm	53 mm	4 Stk	4,560 kg
JTAW5334-1050-A4KCE	170 mm	350 mm	34 mm	53 mm	5 Stk	5,960 kg
JTAW5334-3000-A4KCE	170 mm	350 mm	34 mm	53 mm	13 Stk	16,860 kg
JTAW5334-6000-A4KCE	170 mm	6000 mm	34 mm	53 mm	25 Stk	5,599 kg

H: installation height

L: length

H_p: profile height

B_p: profile width

OPTIONAL ACCESSORIES

JGM B, JKZS



, ETA-09/0338



, EPD-JDL-20200260-IBB1-DE

