



JTA W 72/48

Anchor channel, hot-rolled, with round or I anchor

The anchor channel JTA W 72/48 is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanised steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JA M20 - JA M30. The profile is 72 mm wide and 48 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	H	L	H _p	B _p	W	
JTAW7248-0150-FVKCE	195 mm	150 mm	48 mm	72 mm	2 Stk	2,062 kg
JTAW7248-0200-FVKCE	195 mm	200 mm	48 mm	72 mm	2 Stk	2,548 kg
JTAW7248-0250-FVKCE	195 mm	250 mm	48 mm	72 mm	2 Stk	3,035 kg
JTAW7248-0300-FVKCE	195 mm	300 mm	48 mm	72 mm	2 Stk	3,521 kg
JTAW7248-0350-FVKCE	195 mm	350 mm	48 mm	72 mm	2 Stk	4,007 kg
JTAW7248-0400-FVKCE	195 mm	400 mm	48 mm	72 mm	3 Stk	4,795 kg
JTAW7248-0550-FVKCE	195 mm	550 mm	48 mm	72 mm	3 Stk	6,254 kg
JTAW7248-0800-FVKCE	195 mm	800 mm	48 mm	72 mm	4 Stk	8,988 kg
JTAW7248-1050-FVKCE	195 mm	1050 mm	48 mm	72 mm	5 Stk	11,721 kg
JTAW7248-6000-FVKCE	195 mm	6000 mm	48 mm	72 mm	21 Stk	10,783 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	L	H _p	B _p	W	
JTAW7248-6000-A4KCE	195 mm	6000 mm	48 mm	72 mm	21 Stk	9,990 kg

H: installation height

L: length

H_p: profile height

B_p: profile width

Page 1



W: Weight per storage unit

OPTIONAL ACCESSORIES

JGM A

ETA

, ETA-09/0338



, EPD-JDL-20200260-IBB1-DE

