

JTB-uni

Profiled metal sheet channel rail for fastening profiled sheets to reinforced concrete components

The profiled metal sheet channel JTB-uni is approved by the building supervisory authority (technical approval number: Z-21.4-161. It is made of hot-dip galvanized steel (fv) or stainless steel (A4). With a bearing length of 3000 mm, the channel is available with a profile width of 60 mm. The profile height is 22 mm, the material thickness is 3 mm. Our end anchors are certified as well and available for customized cut-to-length channels. These are fastened to the channels with self-tapping bolts. The filling is made of polystyrene (PS).



steel, batch/hot-dip galvanized

Products	L	H _P	B _P	A		W
TBBR150 FVG-3000	3000 mm	22 mm	60 mm	2,97 cm ²	20 Stk	2,510 kg
TBBR450 FVG-3000	3000 mm	22 mm	60 mm	2,97 cm ²	8 Stk	2,380 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L	H _P	B_{P}	Α		W
TBBR150 A4G-3000	3000 mm	22 mm	60 mm	2,97 cm ²	20 Stk	2,510 kg
TBBR450 A4G-3000	3000 mm	22 mm	60 mm	2,97 cm ²	8 Stk	2,380 kg

L: length

H_p: profile height
B_p: profile width
A: cross section area
W: Weight per storage unit

DETAIL AND APPLICATION IMAGES






Page 1

PohlCon GmbH Nobelstraße 51 | 12057 Berlin Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

PRODUCT INFORMATION



OPTIONAL ACCESSORIES

JTBEB



, Z-21.4-161





Page 2