



## JVB-ZS

### Connection straps

The toothed connection straps JVB-ZS with welded-on bolts are suitable for transmitting tensile and compressive forces. They are available in various lengths and made of either galvanised steel or stainless steel. The series 12 connection strap JVB-ZS is suitable for profiles of the anchor channels JTA K 28/15. Series 18 is suitable for K 38/17 rail profiles.

| Products      | H    | B     | L      | L1    | L2     | weight   |
|---------------|------|-------|--------|-------|--------|----------|
| JVB115ZS12 A4 | 5 mm | 30 mm | 125 mm | 10 mm | 115 mm | 0,159 kg |
| JVB115ZS12 GV | 5 mm | 30 mm | 125 mm | 10 mm | 115 mm | 0,159 kg |
| JVB140ZS12 A4 | 5 mm | 30 mm | 147 mm | 10 mm | 140 mm | 0,188 kg |
| JVB140ZS12 GV | 5 mm | 30 mm | 147 mm | 10 mm | 140 mm | 0,188 kg |
| JVB140ZS18 A4 | 5 mm | 30 mm | 147 mm | 12 mm | 140 mm | 0,201 kg |
| JVB140ZS18 GV | 5 mm | 30 mm | 147 mm | 12 mm | 140 mm | 0,201 kg |
| JVB165ZS12 A4 | 5 mm | 30 mm | 172 mm | 10 mm | 165 mm | 0,217 kg |
| JVB165ZS12 GV | 5 mm | 30 mm | 172 mm | 10 mm | 165 mm | 0,217 kg |
| JVB165ZS18 A4 | 5 mm | 30 mm | 172 mm | 12 mm | 165 mm | 0,230 kg |
| JVB165ZS18 GV | 5 mm | 30 mm | 172 mm | 12 mm | 165 mm | 0,230 kg |
| JVB190ZS12 A4 | 5 mm | 30 mm | 197 mm | 10 mm | 190 mm | 0,246 kg |
| JVB190ZS12 GV | 5 mm | 30 mm | 197 mm | 10 mm | 190 mm | 0,246 kg |
| JVB190ZS18 A4 | 5 mm | 30 mm | 197 mm | 12 mm | 190 mm | 0,260 kg |
| JVB190ZS18 GV | 5 mm | 30 mm | 197 mm | 12 mm | 190 mm | 0,260 kg |
| JVB215ZS12 A4 | 5 mm | 30 mm | 122 mm | 10 mm | 215 mm | 0,276 kg |
| JVB215ZS12 GV | 5 mm | 30 mm | 122 mm | 10 mm | 215 mm | 0,276 kg |
| JVB215ZS18 A4 | 5 mm | 30 mm | 122 mm | 12 mm | 215 mm | 0,289 kg |
| JVB215ZS18 GV | 5 mm | 30 mm | 122 mm | 12 mm | 215 mm | 0,289 kg |

**H:** height  
**B:** width



# PRODUCT INFORMATION

---

**L:** length  
**L1:** length 1  
**L2:** length 2

