


JXA W 64/44

Anchor channel, hot-rolled, toothed, with round or I anchor



The anchor channel JXA W 64/44 is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanized steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JXE M20 - JXE M24. The profile is 64 mm wide and 44 mm high. The filling is made of polyethylene (PE).



steel, batch/hot-dip galvanized

Products	H	L	H _p	B _p		weight
JXAW6444-0150-FVK	190 mm	150 mm	44 mm	64 mm	2 Stk	1,800 kg
JXAW6444-0200-FVK	190 mm	200 mm	44 mm	64 mm	2 Stk	2,203 kg
JXAW6444-0250-FVK	190 mm	250 mm	44 mm	64 mm	2 Stk	2,607 kg
JXAW6444-0300-FVK	190 mm	300 mm	44 mm	64 mm	2 Stk	3,010 kg
JXAW6444-0350-FVK	190 mm	350 mm	44 mm	64 mm	3 Stk	3,709 kg
JXAW6444-0400-FVK	190 mm	400 mm	44 mm	64 mm	3 Stk	4,112 kg
JXAW6444-6000-FVK	190 mm	6000 mm	44 mm	64 mm	25 Stk	9,296 kg

H: installation height

L: length

H_p: profile height

B_p: profile width

ETA

, ETA-09/0338



, EPD-JDL-20200260-IBB1-DE

Page 1

PohlCon

PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

