


JXD M12

Toothed t-bolt



JXD M12 have the general Building authority approval Z-21.4-1690. They are used in conjunction with W 29/20 toothed anchor channels and mounting channels and are made of hot-dip galvanised steel or stainless steel. Another feature of the bolts are the two notches at the end of the shaft. The JXD M12 are available in different lengths. The nuts are included.

AbZ

stainless steel, UNS S31803

Products	L	weight
JXD1240 FA-70	40 mm	0,062 kg
JXD1260 FA-70	60 mm	0,076 kg
JXD1280 FA-70	80 mm	0,091 kg

steel, galvanic zinc plated

Products	L	weight
JXD1230 8.8 GV	30 mm	8,8 0,054 kg
JXD1250 8.8 GV	50 mm	8,8 0,068 kg
JXD12100 8.8 GV	100 mm	8,8 0,105 kg

steel, batch/hot-dip galvanized

Products	L	weight
JXD1230 8.8 FV	30 mm	8,8 0,057 kg
JXD1240 8.8 FV	40 mm	8,8 0,064 kg
JXD1250 8.8 FV	50 mm	8,8 0,072 kg
JXD1260 8.8 FV	60 mm	8,8 0,079 kg
JXD1280 8.8 FV	80 mm	8,8 0,093 kg

Page 1



PRODUCT INFORMATION

Products	L		weight
JXD12100 8.8 FV	100 mm	8,8	0,108 kg
JXD12150 8.8 FV	150 mm	8,8	0,144 kg

L: length



, Z-21.4-1690

