

JZM K 41/22

Mounting channels, cold-formed, toothed

The mounting channel JZM K 41/22 is made of hot-dip galvanised steel (fv), stainless steel (A4) or rolled plain steel (wb). It has a static load-bearing capacity of the normal force (NRd) of 7 kN. The mounting channel is available in the standard length of 6000 mm and is paired with the bolts JZS M12 - JZS M16. The profile is 41 mm wide and 22 mm high.

steel, bright rolled

| Products | L | H _P | B _P | A | W |
|----------------|---------|----------------|----------------|-----------------------|-----------|
| ZMK4122 R-6000 | 6000 mm | 22 mm | 41 mm | 2,387 cm ² | 11,244 kg |

steel, batch/hot-dip galvanized

| Products | L | H _P | B _P | A | W |
|-----------------|---------|----------------|----------------|-----------------------|-----------|
| ZMK4122 FV-6000 | 6000 mm | 22 mm | 41 mm | 2,387 cm ² | 12,366 kg |

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

| Products | L | H_{P} | B _P | Α | W |
|-----------------|---------|---------|----------------|-----------------------|-----------|
| ZMK4122 A4-6000 | 6000 mm | 22 mm | 41 mm | 2,387 cm ² | 11,460 kg |

L: length

H_p: profile height
B_p: profile width
A: cross section area
W: Weight per storage unit

Page 1



