



## KHUV 40

Connector, KHU 40

The connector KHUV 40 can be used to connect bracket holders KHU 40 to each other. We provide components in various materials and surface finishes to ensure that the corrosion requirements are met for all sorts of applications.

### steel, galvanic zinc plated

Products	H	B	L	t	weight
KHUV 40GV	41 mm	32 mm	210 mm	2,00 mm	0,437 kg
incl.:					
4 × FRSV 10X20, 4 × SEMS 10					

### steel, continously hot galvanized/Sendzimir process

Products	H	B	L	t	weight
KHUV 40S	41 mm	32 mm	210 mm	2,00 mm	0,449 kg
incl.:					
4 × FRSV 10X20, 4 × SEM 10, 4 × US 10X21					

### steel, batch/hot-dip galvanized

Products	H	B	L	t	weight
KHUV 40F	41 mm	32 mm	210 mm	2,00 mm	0,470 kg
incl.:					
4 × FRSV 10X20F, 4 × SEM 10F, 4 × US 10X21F					



# PRODUCT INFORMATION

---

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	H	B	L	t	weight
KHUV 40E	41 mm	32 mm	210 mm	2,00 mm	0,451 kg
incl.: 4 x SEM 10E, 4 x US 10X21E, 4 x FRSV 10X20E					

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	B	L	t	weight
KHUV 40E4	41 mm	32 mm	210 mm	2,00 mm	0,455 kg
incl.: 4 x FRSV 10X20E4, 4 x SEM 10E4, 4 x US 10X21E4					

**H:** height  
**B:** width  
**L:** length  
**t:** material thickness

## DETAIL AND APPLICATION IMAGES

