



KHUV 57

Connector, KHU 57

The connector KHUV 57 can be used to connect bracket holders KHU 57 to each other. We provide components in various materials and surface finishes to ensure that the corrosion requirements are met for all sorts of applications.

steel, galvanic zinc plated

Products	H	B	L	t	W
KHUV 57GV	58 mm	33 mm	210 mm	2,50 mm	0,586 kg
incl.:					
4 × FRSV 10X20, 4 × SEMS 10					

steel, continously hot galvanized/Sendzimir process

Products	H	B	L	t	W
KHUV 57S	58 mm	33 mm	210 mm	2,50 mm	0,598 kg
incl.:					
4 × FRSV 10X20, 4 × SEM 10, 4 × US 10X21					

steel, batch/hot-dip galvanized

Products	H	B	L	t	W
KHUV 57F	58 mm	33 mm	210 mm	2,50 mm	0,630 kg
incl.:					
4 × FRSV 10X20F, 4 × SEM 10F, 4 × US 10X21F					



PRODUCT INFORMATION

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	H	B	L	t	W
KHUV 57E	58 mm	33 mm	210 mm	2,50 mm	0,601 kg
incl.: 4 x FRSV 10X20E, 4 x SEM 10E, 4 x US 10X21E					

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	B	L	t	W
KHUV 57E4	58 mm	33 mm	210 mm	2,50 mm	0,607 kg
incl.: 4 x FRSV 10X20E4, 4 x SEM 10E4, 4 x US 10X21E4					

H: height
B: width
L: length
t: material thickness
W: Weight per storage unit

DETAIL AND APPLICATION IMAGES

