



KHUV 60

Connector, KHU 60

KHU 60 bracket holders and STU 60/62 vertical ladders can be connected using the connector KHUV 60. The connector is 51 mm high and 210 mm long. We provide components in various materials and surface finishes to ensure that the corrosion requirements are met for all sorts of applications.

steel, galvanic zinc plated

Products	H	B	L	t	W
KHUV 60GV	51 mm	35 mm	210 mm	4,00 mm	0,771 kg
incl.:					
4 × FRSV 10X20, 4 × SEMS 10					

steel, batch/hot-dip galvanized

Products	H	B	L	t	W
KHUV 60F	51 mm	35 mm	210 mm	4,00 mm	0,828 kg
incl.:					
4 × FRSV 10X20F, 4 × SEM 10F, 4 × US 10X21F					

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	H	B	L	t	W
KHUV 60E	51 mm	35 mm	210 mm	4,00 mm	0,787 kg
incl.:					
4 × FRSV 10X20E, 4 × SEM 10E, 4 × US 10X21E					



PRODUCT INFORMATION

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	H	B	L	t	W
KHUV 60E4	51 mm	35 mm	210 mm	4,00 mm	0,796 kg
incl.:					
4 × US 10X21E4, 4 × FRSV 10X20E4, 4 × SEM 10E4					

H: height
B: width
L: length
t: material thickness
W: Weight per storage unit

DETAIL AND APPLICATION IMAGES

