



## KUNEX® AA

Construction joint tape, PVC-P, external

External KUNEX® PVC-P construction joint tape reliably seals joints in concrete structures. It is installed flush with the surface of the concrete component. The construction joint tapes are available in accordance with DIN or with abP (German building code test certificate) in accordance with the factory standard and have 4 - 8 stop anchors depending on the design. The DIN joint tapes are bitumen-compatible.



### factory standard with abP (not bitumen-compatible)

Products	B	H <sub>p</sub>	No. of stop anchors	Band width	Width expansion element	Thickness expansion element	W
120400002693 Kunex AA190 17	190 mm	17 mm	4	190 mm	80 mm	3,7 mm	1,540 kg
120400002695 Kunex AA240 20	240 mm	20 mm	4	240 mm	80 mm	4 mm	2,060 kg
120400002699 Kunex AA240 25	240 mm	25 mm	4	240 mm	80 mm	4 mm	2,150 kg
120400002702 Kunex AA240 35	240 mm	34 mm	4	240 mm	85 mm	4 mm	2,900 kg
120400002706 Kunex AA320 20	320 mm	20 mm	6	320 mm	100 mm	4 mm	2,860 kg
120400002708 Kunex AA320 25	320 mm	25 mm	6	320 mm	100 mm	4 mm	2,800 kg
120400002712 Kunex AA320 35	320 mm	35 mm	6	320 mm	100 mm	4 mm	4,350 kg
120400002716 Kunex AA500 35	500 mm	35 mm	8	500 mm	120 mm	4 mm	5,480 kg

### DIN BV (bitumen-compatible)



# PRODUCT INFORMATION

Products		B	H <sub>p</sub>	No. of stop anchors	Band width	Width expansion element	Thickness expansion element	W
120400002698	Kunex AA240 20 DIN BV	240 mm	20 mm	4	240 mm	80 mm	4 mm	1,900 kg
120400002701	Kunex AA240 25 DIN BV	240 mm	25 mm	4	240 mm	80 mm	4 mm	1,940 kg
120400002705	Kunex AA240 35 DIN BV	240 mm	35 mm	4	240 mm	84 mm	4 mm	2,900 kg
120400002711	Kunex AA320 25 DIN BV	320 mm	25 mm	6	320 mm	100 mm	4 mm	2,650 kg
120400002715	Kunex AA320 35 DIN BV	320 mm	35 mm	6	320 mm	100 mm	4 mm	3,910 kg
120400002719	Kunex AA500 35 DIN BV	500 mm	35 mm	8	500 mm	120 mm	4 mm	5,900 kg

**B:** width

**H<sub>p</sub>:** profile height

**W:** Weight per storage unit

## OPTIONAL ACCESSORIES

Joint Tape Clip



, P-5143/478/13 MPA BS

