



KUNEX® ABS Construction Joint A-V

Formwork element with construction joint tape (interlocking joint)

The component KUNEX® ABS Construction Joint A-V is a formwork element used to install internal KUNEX® joint tapes in waterproof construction joints in reinforced concrete structures. The product is a combination of a cage to hold the joint tape and a KUNEX® joint tape. The design of the formwork element is suitable for forming interlocked joints according to DIN EN 1992-1-1/NA (EC2) with an installation height of 150 to 500 mm. The KUNEX® ABS Construction Joint A-V is made of steel DC04 and is 2400 mm long. Other dimensions are also available on request.



Products	H	for KUNEX Type	W
121800013932 Kunex ABS V A240 BD 150 300	150-300 mm	A240	4,650 kg
121800013933 Kunex ABS V A240 BD 310 500	310-500 mm	A240	6,820 kg
121800013934 Kunex ABS V A320 BD 150 300	150-300 mm	A320	4,750 kg
121800013935 Kunex ABS V A320 BD 310 500	310-500 mm	A320	6,950 kg

H: installation height

W: Weight per storage unit

OPTIONAL ACCESSORIES

KUNEX® A, FB Shuttering Strip A-CV, FB Shuttering Strip AS-CV



, P-5143/478/13 MPA BS

