



KUNEX® DA

Expansion joint tape, PVC-P, external

External KUNEX® PVC-P expansion joint tape reliably seals joints in concrete structures. It is installed flush with the surface of the concrete component. The joint tapes absorb expansion and shear movements and are available according to DIN or with abP (German building code test certificate) in accordance with the factory standard. Depending on the design, they have 4 - 8 stop anchors. DIN joint tapes are available in bitumen-compatible versions on request.



factory standard with abP (not bitumen-compatible)

Products		B	weight
120600002764	Kunex DA190 17	190 mm	1,700 kg
120600002766	Kunex DA240 20	240 mm	2,300 kg
120600002769	Kunex DA240 35	240 mm	3,300 kg
120600002773	Kunex DA320 20	320 mm	2,980 kg
120600016745	Kunex DA320 25	320 mm	3,180 kg
120600002775	Kunex DA320 35	320 mm	4,420 kg
120600002783	Kunex DA500 35	500 mm	5,340 kg

DIN BV (bitumen-compatible)

Products		B	weight
120600002768	Kunex DA240 20 DIN BV	240 mm	2,200 kg
120600002772	Kunex DA240 35 DIN BV	240 mm	2,970 kg
120600016747	Kunex DA320 25 DIN B	320 mm	3,200 kg
120600002778	Kunex DA320 35 DIN BV	320 mm	4,180 kg
120600002786	Kunex DA500 35 DIN BV	500 mm	4,950 kg

DIN (not bitumen-compatible)



PRODUCT INFORMATION

Products		B	weight
120600002777	Kunex DA320 35 DIN	320 mm	4,180 kg
120600002785	Kunex DA500 35 DIN	500 mm	4,850 kg

B: width



, P-5143/478/13 MPA BS

