



KUNEX® FA

Joint sealing strip, PVC-P

KUNEX® PVC-P joint sealing strips are used to seal the surfaces of expansion joints. They are available according to DIN or with abP (German building code test certificate) in accordance with the factory standard and have 2 - 6 stop anchors depending on the version. The DIN joint tapes are bitumen-compatible.



DIN BV (bitumen-compatible)

Products	Type	B	H _p	No. of stop anchors	W
121100002796	Kunex FA50 20 DIN BV grau	50 mm	20 mm	2	1,295 kg
121100002799	Kunex FA50 30 DIN BV grau	50 mm	30 mm	2	1,240 kg
121100002808	Kunex FA90 20 DIN BV grau	90 mm	20 mm	4	2,400 kg
121100002812	Kunex FA95 30 DIN BV grau	95 mm	30 mm	4	2,400 kg
121100002792	Kunex FA130 20 DIN BV GRA	130 mm	20 mm	6	3,000 kg

factory standard with abP (not bitumen-compatible)

Products	Type	B	H _p	No. of stop anchors	W
121100002798	Kunex FA50 20 grau	50 mm	20 mm	2	1,295 kg
121100002801	Kunex FA50 30 grau	50 mm	30 mm	2	1,220 kg
121100002810	Kunex FA90 20 grau	90 mm	20 mm	4	2,200 kg
121100002814	Kunex FA95 30 grau	95 mm	30 mm	4	2,400 kg
121100002794	Kunex FA130 20 grau	130 mm	20 mm	6	3,040 kg

B: width

H_p: profile height

W: Weight per storage unit





, P-5143/478/13 MPA BS

