



KUNEX® Tubular Seal

Crack control element in in-situ concrete and precast walls

KUNEX® star tubes are used as internal sealing for the formation of dummy joints or crack control joints. In accordance with abP (German building code test certificate), they can be used with KUNEX® joint tapes and PENTAFLEX KB® joint sheets. The star tubes are available in lengths from 2500 to 4000 m and are suitable for walls $\leq 240 - 500$ mm thick. Other lengths available on request. The following applies to selecting the appropriate star tube for precast walls: In-situ concrete core = wall thickness.



Products		L	weight
120300002901	Kunex Stern Q60 2500 SG	2500 mm	4,750 kg
120300002902	Kunex Stern Q60 3000 SG	3000 mm	5,700 kg
120300002903	Kunex Stern Q60 4000 SG	4000 mm	7,600 kg
120300002905	Kunex Stern Q88 2500 SG	2500 mm	7,650 kg
120300002906	Kunex Stern Q88 3000 SG	3000 mm	9,180 kg
120300002907	Kunex Stern Q88 4000 SG	4000 mm	12,240 kg
120300002898	Kunex Stern Q175 2500 SG	2500 mm	18,000 kg
120300002899	Kunex Stern Q175 3000 SG	3000 mm	22,000 kg
120300002900	Kunex Stern Q175 4000 SG	4000 mm	29,000 kg

L: length



, P-5146/481/13 MPA BS

