



LGTR 60

Cable ladder separating strip, height = 33 mm

Cables and lines with different functions or voltages can be routed separately from one another in the same vertical ladder or cable ladder using the separating strip LGTR 60. The separating strip is bolted to the ladder three times: in the middle and on the last rungs of the two ends of the separating strip. The separating strip LGTR 60 is suitable for LGG 60 vertical ladders and cable ladders. It is 33 mm high and 3000 mm long. We provide components in various materials and surface finishes to ensure that the corrosion requirements are met for all sorts of applications.

steel, continuously hot galvanized/Sendzimir process

Products	H	L	weight
LGTR 60S	33 mm	3000 mm	1,231 kg
incl.:			
3 × FKS 6X10, 3 × AM16 M6F			

steel, batch/hot-dip galvanized

Products	H	L	weight
LGTR 60F	33 mm	3000 mm	1,737 kg
incl.:			
3 × FKS 6X10E, 3 × AM16 M6F			

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	H	L	weight
LGTR 60E	33 mm	3000 mm	1,627 kg
incl.:			
3 × FKS 6X10E, 3 × AM16 M6E4			



PRODUCT INFORMATION

H: height
L: length

DETAIL AND APPLICATION IMAGES

