



## LGTR 60

Cable ladder separating strip, height = 33 mm

Cables and lines with different functions or voltages can be routed separately from one another in the same vertical ladder or cable ladder using the separating strip LGTR 60. The separating strip is bolted to the ladder three times: in the middle and on the last rungs of the two ends of the separating strip. The separating strip LGTR 60 is suitable for LGG 60 vertical ladders and cable ladders. It is 33 mm high and 3000 mm long. We provide components in various materials and surface finishes to ensure that the corrosion requirements are met for all sorts of applications.

steel, continuously hot galvanized/Sendzimir process

| Products                   | H     | L       | weight   |
|----------------------------|-------|---------|----------|
| LGTR 60S                   | 33 mm | 3000 mm | 1,231 kg |
| incl.:                     |       |         |          |
| 3 × FKS 6X10, 3 × AM16 M6F |       |         |          |

steel, batch/hot-dip galvanized

| Products                    | H     | L       | weight   |
|-----------------------------|-------|---------|----------|
| LGTR 60F                    | 33 mm | 3000 mm | 1,737 kg |
| incl.:                      |       |         |          |
| 3 × FKS 6X10E, 3 × AM16 M6F |       |         |          |

Stainless steel, according to ASTM 304 / BS 304 S 3

| Products                     | H     | L       | weight   |
|------------------------------|-------|---------|----------|
| LGTR 60E                     | 33 mm | 3000 mm | 1,627 kg |
| incl.:                       |       |         |          |
| 3 × FKS 6X10E, 3 × AM16 M6E4 |       |         |          |



# PRODUCT INFORMATION

---

**H:** height  
**L:** length

## DETAIL AND APPLICATION IMAGES

