



LGVB 60

Cable ladder vertical bend, height = 60 mm

The cable tray vertical bend LGVB 60 allows the direction of cable routing to be changed flexibly and vertically. They are suitable for cable ladders with rails 60 mm high and are 200 to 600 mm wide. The bend is pushed into the cable ladder and then bolted in place. The connection cable ladder is then inserted into the end of the formed part and also bolted in place. We provide components in various materials and surface finishes to ensure that the corrosion requirements are met for all sorts of applications.

steel, batch/hot-dip galvanized

Products	H	B		W
LGVB 60-20F	60 mm	200 mm	STEIGEND-FALLEND	2,448 kg
LGVB 60-30F	60 mm	300 mm	STEIGEND-FALLEND	2,748 kg
LGVB 60-40F	60 mm	400 mm	STEIGEND-FALLEND	3,048 kg
LGVB 60-50F	60 mm	500 mm	STEIGEND-FALLEND	3,348 kg
LGVB 60-60F	60 mm	600 mm	STEIGEND-FALLEND	3,628 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	H	B		W
LGVB 60-20E	60 mm	200 mm	STEIGEND-FALLEND	2,352 kg
LGVB 60-30E	60 mm	300 mm	STEIGEND-FALLEND	2,632 kg
LGVB 60-40E	60 mm	400 mm	STEIGEND-FALLEND	2,912 kg
LGVB 60-50E	60 mm	500 mm	STEIGEND-FALLEND	3,192 kg
LGVB 60-60E	60 mm	600 mm	STEIGEND-FALLEND	3,452 kg

H: height
B: width
W: Weight per storage unit



DETAIL AND APPLICATION IMAGES

