



LGVH 60

Cable ladder connector, horizontal, height = 60 mm

Horizontal changes of direction can also be implemented without formed parts. To do so, LGVH 60 horizontal connectors are pushed onto the rails of the cable ladder previously cut to size according to the installation instructions and bolted in place. The connectors can be adjusted to the required angle. The pre-cut connecting rack is then mounted using the connectors. A branch can also be set up in this way. The connector LGVH 60 is 60 mm high corresponding to the cable ladder and 150 mm long. We provide components in various materials and surface finishes to ensure that the corrosion requirements are met for all sorts of applications.

steel, continously hot galvanized/Sendzimir process

Products	H	L	W
LGVH 60S	60 mm	150 mm	0,216 kg
incl.:			
2 x KLS 8X16			

steel, batch/hot-dip galvanized

Products	H	L	W
LGVH 60F	60 mm	150 mm	0,226 kg
incl.:			
2 x KLS 8X16E			

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	H	L	W
LGVH 60E	60 mm	150 mm	0,222 kg
incl.:			
2 x KLS 8X16E			



PRODUCT INFORMATION

H: height
L: length
W: Weight per storage unit

DETAIL AND APPLICATION IMAGES

