



PENTAFLEX® ABS R Floor/Floor

Sealing formwork element as a rough joint

The component PENTAFLEX® ABS R Floor/Floor is a formwork element that is used to create waterproof construction joints in the floor-to-floor connection area of reinforced concrete components. The ABS-R version with a shortened, stiffening lattice girder construction is suitable for forming rough joints. The formwork element is made of DC04 steel and has been verified as watertight up to 5.0 bar. It is 2400 mm long and 80 to 590 mm high. Other length dimensions, e.g. short or conical pieces, are also available on request.



Products		H	W
111700022834	Penta ABS R BD 80 200	2,370 kg	
111700022084	Penta ABS R BD 80 200 2.4 NEW	140-200 mm	2,370 kg
111700022835	Penta ABS R BD 210 250	2,600 kg	
111700022085	Penta ABS R BD 210 250 2.4 NEW	210-250 mm	2,600 kg
111700022836	Penta ABS R BD 260 300	2,820 kg	
111700022086	Penta ABS R BD 260 300 2.4 NEW	260-300 mm	2,820 kg
111700022837	Penta ABS R BD 310 350	3,260 kg	
111700022087	Penta ABS R BD 310 350 2.4 NEW	310-350 mm	3,260 kg
111700022838	Penta ABS R BD 360 400	3,500 kg	
111700022088	Penta ABS R BD 360 400 2.4 NEW	360-400 mm	3,500 kg
111700022839	Penta ABS R BD 410 500	3,990 kg	
111700022089	Penta ABS R BD 410 500 2.4 NEW	410-500 mm	3,990 kg
111700022840	Penta ABS R BD 510 590	4,920 kg	
111700022090	Penta ABS R BD 510 590 2.4 NEW	510-590 mm	4,920 kg

H: installation height
W: Weight per storage unit

OPTIONAL ACCESSORIES

FB Shuttering Strip A-CV, FB Shuttering Strip AS-CV

Page 1



PohlCon GmbH
 Nobelstraße 51 | 12057 Berlin
 Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com



PRODUCT INFORMATION

ETA

, ETA-15/0003

