



## PENTAFLEX® ABS R Floor/Floor

Sealing formwork element as a rough joint

The component PENTAFLEX® ABS R Floor/Floor is a formwork element that is used to create waterproof construction joints in the floor-to-floor connection area of reinforced concrete components. The ABS-R version with a shortened, stiffening lattice girder construction is suitable for forming rough joints. The formwork element is made of DC04 steel and has been verified as watertight up to 5.0 bar. It is 2400 mm long and 80 to 590 mm high. Other length dimensions, e.g. short or conical pieces, are also available on request.



Products		weight
111700022834	Penta ABS R BD 80 200	2,370 kg
111700022084	Penta ABS R BD 80 200 2.4 NEW	2,370 kg
111700022835	Penta ABS R BD 210 250	2,600 kg
111700022085	Penta ABS R BD 210 250 2.4 NEW	2,600 kg
111700022836	Penta ABS R BD 260 300	2,820 kg
111700022086	Penta ABS R BD 260 300 2.4 NEW	2,820 kg
111700022837	Penta ABS R BD 310 350	3,260 kg
111700022087	Penta ABS R BD 310 350 2.4 NEW	3,260 kg
111700022838	Penta ABS R BD 360 400	3,500 kg
111700022088	Penta ABS R BD 360 400 2.4 NEW	3,500 kg
111700022839	Penta ABS R BD 410 500	3,990 kg
111700022089	Penta ABS R BD 410 500 2.4 NEW	3,990 kg
111700022840	Penta ABS R BD 510 590	4,920 kg
111700022090	Penta ABS R BD 510 590 2.4 NEW	4,920 kg

## OPTIONAL ACCESSORIES

FB Shuttering Strip A-CV, FB Shuttering Strip AS-CV



# PRODUCT INFORMATION

---

ETA

, ETA-15/0003

