



PENTAFLEX® ABS R Wall/Wall

Sealing formwork element as a rough joint

The component PENTAFLEX® ABS R Wall/Wall is a formwork element that is used to create waterproof construction joints in the wall-to-wall connection area of reinforced concrete components. The ABS-R version with a shortened, stiffening lattice girder construction is suitable for forming rough joints. The formwork element is made of DC04 steel and has been verified as watertight up to 5.0 bar. It is 2400 mm long and 80 to 590 mm high. Other length dimensions, e.g. short or conical pieces, are also available on request.



Products		weight
111900022894	Penta ABS R W 80 200	2,370 kg
111900022862	Penta ABS R W 80 200 2.4	2,370 kg
111900022895	Penta ABS R W 210 250	2,600 kg
111900022863	Penta ABS R W 210 250 2.4	2,600 kg
111900022896	Penta ABS R W 260 300	2,820 kg
111900022864	Penta ABS R W 260 300 2.4	2,820 kg
111900022897	Penta ABS R W 310 350	3,260 kg
111900022865	Penta ABS R W 310 350 2.4	3,260 kg
111900022898	Penta ABS R W 360 400	3,500 kg
111900022866	Penta ABS R W 360 400 2.4	3,500 kg
111900022899	Penta ABS R W 410 500	3,990 kg
111900022867	Penta ABS R W 410 500 2.4	3,990 kg
111900022900	Penta ABS R W 510 590	4,920 kg
111900022868	Penta ABS R W 510 590 2.4	4,920 kg

ETA

, ETA-15/0003

