



## PENTAFLEX® ABS V-S Wall/Wall

Sealing formwork element, reinforced

The component PENTAFLEX® ABS V-S Wall/Wall is a formwork element that is used to create waterproof construction joints in the wall-to-wall connection area of reinforced concrete components. The ABS-R version with a reinforced lattice girder construction is suitable for interlocking joint versions according to DIN EN 1992-1-1/NA (EC2). The formwork element is made of DC04 steel and has been verified as watertight up to 5.0 bar. It is 2400 mm long and 600 to 1990 mm high. Other length dimensions, e.g. short or conical pieces, are also available on request.



Products		H	W
112200022098	Penta ABS VS BD 600 690	600-690 mm	4,820 kg
112200022100	Penta ABS VS BD 800 890	800-890 mm	6,780 kg
112200022102	Penta ABS VS BD 1000 1090	1000-1090 mm	8,960 kg
112200022104	Penta ABS VS BD 1200 1290	1200-1290 mm	9,840 kg
112200022106	Penta ABS VS BD 1400 1490	1400-1490 mm	11,380 kg
112200022108	Penta ABS VS BD 1600 1690	1600-1690 mm	14,010 kg
112200022110	Penta ABS VS BD 1800 1890	1800-1890 mm	14,980 kg

**H:** installation height

**W:** Weight per storage unit

ETA

, ETA-15/0003

