



PENTAFLEX® FTS-Corner

Pre-cast concrete crack control element with joint sheet (corner section)

PENTAFLEX® FTS-Corner crack control elements for corner joints consist of PENTAFLEX KB® joint sheets with a wing made of galvanised sheet steel. They come in lengths of 2.50, 2.75 and 3.00 m as standard. The PENTAFLEX® FTS joint element is available for walls of any thickness. Standard elements for 240 - 250 or 300 mm thick walls are kept in stock. The elements are supplied ready for installation. When using PENTAFLEX® FTS-Corner elements, PENTAFLEX KB® corner elements must be installed in the floor slab.



Products		L	weight
110600004396	Penta FTS Eck 240 280 2.5	2500 mm	2,000 kg
110600004397	Penta FTS Eck 240 280 2.75	2750 mm	2,000 kg
110600004398	Penta FTS Eck 240 280 3.0	3000 mm	2,000 kg
110600004399	Penta FTS Eck 290 340 2.5	2500 mm	2,150 kg
110600004400	Penta FTS Eck 290 340 2.75	2750 mm	2,150 kg
110600004401	Penta FTS Eck 290 340 3.0	3000 mm	2,150 kg
110600004402	Penta FTS Eck 350 400 2.5	2500 mm	2,300 kg
110600004403	Penta FTS Eck 350 400 2.75	2750 mm	2,300 kg
110600004404	Penta FTS Eck 350 400 3.0	3000 mm	2,300 kg

L: length

OPTIONAL ACCESSORIES

PENTAFLEX KB® Corner



, ETA-15/0003



AbP

, P-5120/231/09 MPA-BS

