



## PENTAFLEX® OBS G-S Floor

In-situ concrete crack control element with joint sheet (smooth joint)

PENTAFLEX® OBS G-S Floor floor panel elements for smooth joints (according to EC 2) consist of PENTAFLEX KB® joint sheets with wings made of galvanised sheet steel. They come in lengths of 2500 mm as standard. The standard installation dimension is 80 - 1000 mm.



Products	H	L	W
110700020328 Penta OBS X BD 80 200	80-200 mm	2750 mm	2,380 kg
110700020330 Penta OBS X BD 210 250	210-250 mm	2750 mm	2,600 kg
110700020325 Penta OBS X BD 260 300	260-300 mm	2750 mm	2,820 kg
110700020326 Penta OBS X BD 310 350	310-350 mm	2750 mm	3,260 kg
110700020327 Penta OBS X BD 360 400	360-400 mm	2750 mm	3,500 kg
110700020332 Penta OBS X BD 410 500	410-500 mm	2750 mm	3,990 kg
110700020329 Penta OBS X BD 510 600	510-600 mm	2750 mm	4,920 kg
110700020316 Penta OBS X BD 610 700	610-700 mm	2750 mm	5,410 kg
110700020320 Penta OBS X BD 710 800	710-800 mm	2750 mm	9,870 kg
110700020317 Penta OBS X BD 810 900	810-900 mm	2750 mm	10,390 kg
110700020318 Penta OBS X BD 910 1000	910-1000 mm	2750 mm	10,920 kg

**H:** installation height

**L:** length

**W:** Weight per storage unit

ETA

, ETA-15/0003

AbP



, P-5120/231/09 MPA-BS

