



PENTAFLEX® OBS V-S Floor

In-situ concrete crack control element with joint sheet (interlocking joint)

PENTAFLEX® OBS V-S Floor floor panel elements for interlocked joints consist of PENTAFLEX KB® joint sheets with wings made of galvanized sheet steel. They come in lengths of 2500 mm as standard. The standard installation dimension is 140 - 1000 mm.



Products	H	L	W
110700019963 Penta OBS-V B 260 300	260-300 mm	2750 mm	2,960 kg
110700019961 Penta OBS V B 140 200	140-200 mm	2750 mm	2,610 kg
110700019962 Penta OBS V B 210 250	210-250 mm	2750 mm	2,740 kg
110700019964 Penta OBS V B 310 350	310-350 mm	2750 mm	3,340 kg
110700019965 Penta OBS V B 360 400	360-400 mm	2750 mm	3,590 kg
110700020319 Penta OBS XV BD 410 500	410-500 mm	2750 mm	4,080 kg
110700020331 Penta OBS XV BD 510 600	510-600 mm	2750 mm	5,460 kg
110700020322 Penta OBS XV BD 610 700	610-700 mm	2750 mm	5,950 kg
110700020321 Penta OBS XV BD 710 800	710-800 mm	2750 mm	8,900 kg
110700020323 Penta OBS XV BD 810 900	810-900 mm	2750 mm	9,390 kg
110700020324 Penta OBS XV BD 910 1000	910-1000 mm	2750 mm	9,880 kg

H: installation height

L: length

W: Weight per storage unit

ETA

, ETA-15/0003

AbP



, P-5120/231/09 MPA-BS

