



PENTAFLEX® OBS Wall

In-situ concrete crack control element with joint sheet

PENTAFLEX® OBS Wall wall elements consist of PENTAFLEX KB® joint sheets with wings made of galvanised sheet steel. They come in lengths of 2.50, 2.75 and 3.00 m as standard. The standard installation dimension is 140 and 180 mm for walls 240 - 250 and 300 mm thick respectively. Larger installation dimensions are possible on request. The wall elements are supplied ready for installation.



| Products | | L | W |
|--------------|-------------------------|---------|----------|
| 110700004416 | Penta OBS Fuge 140 2.5 | 2500 mm | 2,450 kg |
| 110700004417 | Penta OBS Fuge 140 2.75 | 2750 mm | 2,450 kg |
| 110700004418 | Penta OBS Fuge 140 3.0 | 3000 mm | 2,450 kg |
| 110700004419 | Penta OBS Fuge 160 2.5 | 2500 mm | 2,525 kg |
| 110700004420 | Penta OBS Fuge 160 2.75 | 2750 mm | 2,525 kg |
| 110700004421 | Penta OBS Fuge 160 3.0 | 3000 mm | 2,525 kg |
| 110700004422 | Penta OBS Fuge 180 2.5 | 2500 mm | 2,600 kg |
| 110700004423 | Penta OBS Fuge 180 2.75 | 2750 mm | 2,600 kg |
| 110700004424 | Penta OBS Fuge 180 3.0 | 3000 mm | 2,600 kg |

L: length

W: Weight per storage unit

ETA

, ETA-15/0003

AbP

, P-5120/231/09 MPA-BS

