



## PENTAFLEX® Transwand DM-PP

### Waterproof wall lead-through

PENTAFLEX® Transwand DM-PP is a waterproof wall lead-through for cast-in-place or precast walls. It consists of a PP pipe and is available with a double sleeve. The pipe diameter DN is 110 - 160 mm. The bushing is suitable for walls 240 - 500 mm thick and a water pressure of up to 5.0 bar.

Products	weight
110900013045 Twand PP 110 240 DM	0,519 kg
110900013046 Twand PP 110 250 DM	0,530 kg
110900013047 Twand PP 110 300 DM	0,586 kg
110900013049 Twand PP 110 350 DM	0,642 kg
110900013051 Twand PP 110 360 DM	0,653 kg
110900013052 Twand PP 110 365 DM	0,659 kg
110900013054 Twand PP 110 400 DM	0,698 kg
110900013056 Twand PP 110 500 DM	0,810 kg
110900013073 Twand PP 125 240 DM	0,663 kg
110900013074 Twand PP 125 250 DM 115 mm	0,680 kg
110900013077 Twand PP 125 350 DM	0,852 kg
110900013081 Twand PP 125 400 DM	0,938 kg
110900013103 Twand PP 160 350 DM	1,819 kg
110900013107 Twand PP 160 400 DM	2,036 kg
110900013109 Twand PP 160 500 DM	2,470 kg

