



## PENTAFLEX® Transwand PP

### Waterproof wall lead-through

PENTAFLEX® Transwand PP is a waterproof wall lead-through for cast-in-place or precast walls. It consists of a PP pipe and is available with sleeve and polystyrene ring. The pipe diameter DN is 110 - 200 mm. The bushing is suitable for walls 240 - 500 mm thick and a water pressure of up to 5.0 bar.

Products		W
110900013032	Twand PP 110 200	0,474 kg
110900013035	Twand PP 110 300	0,586 kg
110900013037	Twand PP 110 350	0,642 kg
110900013039	Twand PP 110 365	0,659 kg
110900013041	Twand PP 110 400	0,698 kg
110900013043	Twand PP 110 500	0,810 kg
110900013060	Twand PP 125 200	0,594 kg
110900013061	Twand PP 125 240	0,663 kg
110900013062	Twand PP 125 250	0,680 kg
110900013065	Twand PP 125 350	0,852 kg
110900013069	Twand PP 125 400	0,938 kg
110900013071	Twand PP 125 500	1,110 kg
110900013090	Twand PP 160 250	1,385 kg
110900013091	Twand PP 160 300	1,602 kg
110900013095	Twand PP 160 365	1,884 kg
110900013099	Twand PP 160 500	2,470 kg
110900013112	Twand PP 200 300	2,416 kg
110900013114	Twand PP 200 350	2,752 kg
110900013115	Twand PP 200 365	2,853 kg
110900013117	Twand PP 200 400	3,088 kg

W: Weight per storage unit





PohlCon GmbH  
Nobelstraße 51 | 12057 Berlin  
Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | [contact@pohlcon.com](mailto:contact@pohlcon.com)

