



RU-HW

Cable clamp for fastening to round and flat profiles

The HF cable clamp RU-HW with full-surface pressure trough made of galvanised steel and plastic half troughs made of polystyrene can route fibre-optic/high-frequency cables with a maximum diameter of 1 5/8 inches. It is suitable for fastening to round and flat profiles made from material max. 22 mm thick. We provide components in various materials and surface finishes to ensure that various requirements for different areas of application are met.

steel, zinc plated

Products	D	H _{max}	B	D	cables	W
20 RU-HW	17 mm	53 mm	20 mm	1/2 Zoll	1	0,053 kg
32 RU-HW	29 mm	68 mm	32 mm	7/8 Zoll	1	0,102 kg
44 RU-HW	39 mm	83 mm	44 mm	1 1/4 Zoll	1	0,141 kg
56 RU-HW	51 mm	106 mm	56 mm	1 5/8 Zoll	1	0,181 kg
20/2 RU-HW	17 mm	73 mm	20 mm	1/2 Zoll	2	0,079 kg
32/2 RU-HW	29 mm	102 mm	32 mm	7/8 Zoll	2	0,157 kg
44/2 RU-HW	39 mm	129 mm	44 mm	1 1/4 Zoll	2	0,223 kg
56/2 RU-HW	51 mm	164 mm	56 mm	1 5/8 Zoll	2	0,283 kg
20/3 RU-HW	17 mm	93 mm	20 mm	1/2 Zoll	3	0,100 kg
32/3 RU-HW	29 mm	136 mm	32 mm	7/8 Zoll	3	0,213 kg
44/3 RU-HW	39 mm	176 mm	44 mm	1 1/4 Zoll	3	0,314 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	D	H _{max}	B	D	cables	W
20 RU-HW-E	17 mm	53 mm	20 mm	1/2 Zoll	1	0,008 kg
32 RU-HW-E	29 mm	68 mm	32 mm	7/8 Zoll	1	0,103 kg
44 RU-HW-E	39 mm	83 mm	44 mm	1 1/4 Zoll	1	0,141 kg
56 RU-HW-E	51 mm	106 mm	56 mm	1 5/8 Zoll	1	0,182 kg
20/2 RU-HW-E	17 mm	73 mm	20 mm	1/2 Zoll	2	0,076 kg

Page 1



PRODUCT INFORMATION

Products	D	H _{max}	B	D	cables	W
32/2 RU-HW-E	29 mm	102 mm	32 mm	7/8 Zoll	2	0,155 kg
44/2 RU-HW-E	39 mm	129 mm	44 mm	1 1/4 Zoll	2	0,215 kg
56/2 RU-HW-E	51 mm	164 mm	56 mm	1 5/8 Zoll	2	0,287 kg
20/3 RU-HW-E	17 mm	93 mm	20 mm	1/2 Zoll	3	0,000 kg
32/3 RU-HW-E	29 mm	136 mm	32 mm	7/8 Zoll	3	0,208 kg
44/3 RU-HW-E	39 mm	176 mm	44 mm	1 1/4 Zoll	3	0,297 kg

D: clamping range
H_{max}: maximum height
B: width
D: diameter
cables: max. number of cables
W: Weight per storage unit

DETAIL AND APPLICATION IMAGES

