



S-HW

Cable clamp for fastening to angle profiles

The HF cable clamp S-HW with full-surface pressure trough made of galvanised steel and plastic half troughs made of polystyrene can route fibre-optic/high-frequency cables with a maximum diameter of 1 5/8 inches. They are suitable for attachment to angle profiles with a leg length of max. 40 mm. We provide components in various materials and surface finishes to ensure that various requirements for different areas of application are met.

steel, zinc plated

Products	D	H _{max}	B	D	cables	W
20 S-HW	17 mm	53 mm	20 mm	1/2 Zoll	1	0,052 kg
32 S-HW	29 mm	68 mm	32 mm	7/8 Zoll	1	0,096 kg
44 S-HW	39 mm	83 mm	44 mm	1 1/4 Zoll	1	0,145 kg
56 S-HW	51 mm	106 mm	56 mm	1 5/8 Zoll	1	0,182 kg
20/2 S-HW	17 mm	73 mm	20 mm	1/2 Zoll	2	0,076 kg
32/2 S-HW	29 mm	102 mm	32 mm	7/8 Zoll	2	0,139 kg
20/3 S-HW	17 mm	93 mm	20 mm	1/2 Zoll	3	0,097 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	D	H _{max}	B	D	cables	W
20 S-HW-E	17 mm	53 mm	20 mm	1/2 Zoll	1	0,049 kg
32 S-HW-E	29 mm	68 mm	32 mm	7/8 Zoll	1	0,086 kg
44 S-HW-E	39 mm	83 mm	44 mm	1 1/4 Zoll	1	0,131 kg
56 S-HW-E	51 mm	106 mm	56 mm	1 5/8 Zoll	1	0,167 kg
20/2 S-HW-E	17 mm	73 mm	20 mm	1/2 Zoll	2	0,072 kg
32/2 S-HW-E	29 mm	102 mm	32 mm	7/8 Zoll	2	0,134 kg
44/2 S-HW-E	39 mm	129 mm	44 mm	1 1/4 Zoll	2	0,179 kg
56/2 S-HW-E	51 mm	164 mm	56 mm	1 5/8 Zoll	2	0,255 kg
20/3 S-HW-E	17 mm	93 mm	20 mm	1/2 Zoll	3	0,087 kg

Page 1



PRODUCT INFORMATION

Products	D	H _{max}	B	D	cables	W
32/3 S-HW-E	29 mm	136 mm	32 mm	7/8 Zoll	3	0,159 kg
44/3 S-HW-E	39 mm	176 mm	44 mm	1 1/4 Zoll	3	0,269 kg

D: clamping range

H_{max}: maximum height

B: width

D: diameter

cables: max. number of cables

W: Weight per storage unit

DETAIL AND APPLICATION IMAGES

