


## SEMS

Hexagonal nut with flange, DIN EN 1661



Hexagon nuts with flange SEMS (in line with DIN EN 1661) are used in combination with suitable bolts in numerous applications, e.g. when installing ceiling brackets, storm protection brackets for cable trays, cable ladders or outlet plates. The nuts are available in threads M6 to M10. We provide components in various materials and surface finishes to ensure that various corrosion protection requirements for different areas of application are met.

steel, galvanic zinc plated

Products	ø	D	t	SW	W
SEMS 6	6 mm	14 mm	5,50 mm	10 mm	0,002 kg
SEMS 8	8 mm	17 mm	7,50 mm	13 mm	0,006 kg
SEMS 10	10 mm	21 mm	9,50 mm	17 mm	0,010 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	ø	D	t	SW	W
SEMS 6E	6 mm	14 mm	5,50 mm	10 mm	0,003 kg
SEMS 8E	8 mm	17 mm	7,50 mm	13 mm	0,006 kg
SEMS 10E	10 mm	21 mm	9,50 mm	15 mm	0,011 kg

Ø: thread diameter

D: diameter

t: material thickness

SW: wrench size

W: Weight per storage unit

## DETAIL AND APPLICATION IMAGES



