


## SEMSS

Hexagon nut, self-locking, DIN 985



Self-locking hexagon nuts SEMSS (in line with DIN 985) are used in combination with suitable bolts in numerous applications, e.g. when installing floor and side connectors for wide-span trays or fastening storm protection brackets on mesh cable trays. The hexagon nuts are available in threads M6 to M10. We provide components in various materials and surface finishes to ensure that various corrosion protection requirements for different areas of application are met.

steel, galvanic zinc plated

Products	ø	t	SW	W
SEMSS 5	5 mm	5 mm	8 mm	0,002 kg
SEMSS 6	6 mm	6,00 mm	10 mm	0,002 kg
SEMSS 8	8 mm	8,00 mm	13 mm	0,005 kg
SEMSS 10	10 mm	10,00 mm	17 mm	0,010 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	ø	t	SW	W
SEMSS 6E	6 mm	8,00 mm	13 mm	0,002 kg
SEMSS 8E	8 mm	8,00 mm	13 mm	0,005 kg
SEMSS 10E	10 mm	10,00 mm	17 mm	0,010 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	ø	t	SW	W
SEMSS 6E4	6 mm	6,00 mm	10 mm	0,002 kg
SEMSS 8E4	8 mm	8,00 mm	13 mm	0,005 kg
SEMSS 10E4	10 mm	10,00 mm	17 mm	0,010 kg

Page 1



# PRODUCT INFORMATION

---

Ø: thread diameter  
t: material thickness  
SW: wrench size  
W: Weight per storage unit

## DETAIL AND APPLICATION IMAGES

