



SLVV

Ship cable ladder vertical connectors

To create vertical changes of direction, SLVV ship cable ladder vertical connectors are pushed onto the side rails of the ship cable ladder and bolted in place according to the installation instructions. The connectors can be adjusted to the required angle. The connecting rack is then mounted using the connectors. The vertical connector is 38 mm high corresponding to the ship cable ladder and 180 mm long. We provide components in various materials and surface finishes to ensure that a wide range of corrosion requirements are met and that additional protective measures can be taken.

coated

Products	H	B	weight
SLVV M	38 mm	180 mm	0,000 kg
incl.:			
2 × KLS 10X20F, 1 × SES 10X20F, 1 × US 10X21F, 1 × SEM 10F			

steel, bright rolled

Products	H	B	weight
SLVV B	38 mm	180 mm	0,000 kg
incl.:			
1 × SES 10X20F, 1 × US 10X21F, 1 × SEM 10F, 2 × KLS 10X20F			

steel, batch/hot-dip galvanized

Products	H	B	weight
SLVV F	38 mm	180 mm	0,304 kg
incl.:			
2 × KLS 10X20F, 1 × SES 10X20F, 1 × US 10X21F, 1 × SEM 10F			



PRODUCT INFORMATION

H: height
B: width

DETAIL AND APPLICATION IMAGES

